



Slovak Society of Chemical Engineering
Institute of Chemical and Environmental Engineering
Slovak University of Technology in Bratislava

PROCEEDINGS

51st International Conference of the Slovak Society of Chemical Engineering SSCHE 2025

Hotel DRUŽBA
Jasná, Demänovská Dolina, Slovakia
May 27 - 30, 2025

Editors: Assoc. Prof. Mário Mihaľ

ISBN: 978-80-8208-158-2, EAN: 9788082081582

Published by the Faculty of Chemical and Food Technology Slovak Technical University in Bratislava in Slovak Chemistry Library for the Institute of Chemical and Environmental Engineering; Radlinského 9, 812 37 Bratislava, 2024

Mócová, M., Švistun, L., Variny, M.: Hydrogen Strategy for RED III Compliance in a Refinery, Editors: Mihaľ, M., In *51st International Conference of the Slovak Society of Chemical Engineering SSCHE 2025*, Jasná, Demänovská Dolina, Slovakia, 2025.

Hydrogen Strategy for RED III Compliance in a Refinery

Martina Mócová¹, Ladislav Švistun², Miroslav Variny¹

¹*Institute of Chemical and Environmental Engineering, FCHPT STU, Bratislava, Slovakia*

²*SLOVNAFT, a.s., Bratislava, Slovakia*

e-mail: mocova.martina@gmail.com

Key words: hydrogen, RFNBO, RED III, MCDA.

The European Union aims to achieve carbon neutrality by 2050. As part of the path toward a climate-neutral economy, environmental regulations are being continuously introduced and tightened. The latest Renewable Energy Directive (RED III), set to take effect from 2030, focuses on the energy, industry, and transport sectors. The Directive specifies the target share of renewable fuels in overall fuel consumption across these sectors. Notably, RED III requires a minimum 5.5% share of biofuels and 1% share of renewable fuels of non-biological origin (RFNBO), which can be generated through electrolysis using renewable energy. Hydrogen is an important component in refineries where it is utilized for polypropylene production and removal of undesirable elements such as sulfur or nitrogen from feedstocks. Currently, majority of hydrogen is produced by reforming processes. To comply with the RED III targets, a portion of hydrogen production should be substituted with RFNBO. In this work, several methods for achieving RED III targets are analyzed. RFNBO can be produced directly within the refinery. This can involve either generating a quantity of RFNBO sufficient to meet the refinery's own needs or facilitating production within the Slovak Republic. Alternatively, RFNBO can be sourced from countries where renewable energy is less expensive. Green ammonia may serve as an effective hydrogen carrier, which can be stored and subsequently decomposed in the refinery. Another scenario considers a situation in which RFNBO is neither produced nor purchased, which would incur penalties. To meet biofuel targets, biomethane can be acquired, contributing to lower carbon emissions. Additionally, hydrogen can be produced via thermal pyrolysis of natural gas or biomethane. During the pyrolysis reactions, CO₂ is not directly produced. Instead, solid carbon is formed, resulting in a lower carbon footprint compared to reforming process. Combinations of strategic pathways are evaluated and compared using a Multi-Criteria Decision Analysis (MCDA). The objective is to identify viable strategy for integrating renewable fuel solutions into refinery operations.

Acknowledgement

This work was supported by the Slovak Scientific Agency, grant no. VEGA 1/0151/24. Support by Slovak Society of Chemical Engineering is gratefully acknowledged.