



Slovak Society of Chemical Engineering
Institute of Chemical and Environmental Engineering
Slovak University of Technology in Bratislava

PROCEEDINGS

51st International Conference of the Slovak Society of Chemical Engineering SSCHE 2025

Hotel DRUŽBA
Jasná, Demänovská Dolina, Slovakia
May 27 - 30, 2025

Editors: Assoc. Prof. Mário Mihaľ

ISBN: 978-80-8208-158-2, EAN: 9788082081582

Published by the Faculty of Chemical and Food Technology Slovak Technical University in Bratislava in Slovak Chemistry Library for the Institute of Chemical and Environmental Engineering; Radlinského 9, 812 37 Bratislava, 2024

Gnatowski, P., Kucińska-Lipka, J.: Biodegradable active substances release systems, Editors: Mihaľ, M., In *51st International Conference of the Slovak Society of Chemical Engineering SSCHE 2025*, Jasná, Demänovská Dolina, Slovakia, 2025.

Biodegradable active substances release systems

Przemysław Gnatowski^{1,2*}, Justyna Kucińska-Lipka¹

¹ *Department of Polymer Technology, Faculty of Chemistry, Gdańsk University of Technology,
Narutowicza 11/12, 80-233 Gdańsk, Poland,*

² *Department of Environmental Toxicology, Faculty of Health Sciences with the Institute of
Maritime and Tropical Medicine, Medical University of Gdańsk, Dębowa 23A, Gdańsk 80-204,*

**e-mail: przemyslaw.gnatowski@pg.edu.pl*

Key words: polyurethane, curcumin, biodegradation, drug delivery systems

Many of the modern drugs developed to combat various diseases cannot be easily used in postoperative treatment due to difficulties in achieving therapeutic concentrations of active agents in the injured areas. This problem is particularly acute in places with limited access, such as the urinary tract, brain, or paranasal sinuses. In order to meet the needs of both patients and doctors, a biodegradable polyurethane-based implant and hydrogel agar-based coating were developed to be placed in the right place during surgery. Combination of modeling, mechanical (bending, compression), structural (FTIR), thermal (DSC, MFR), surface (contact angle), microscopic (optical), degradation (2 M HCl, 5 M NaOH and 0.01 M PBS) analysis, release of the active substance and cell viability (MTT) allowed to assess the suitability of the developed material for the production of implants. Obtained polyurethanes were characterized with high mechanical strength ($\sigma > 20$ MPa), optimal biodegradability (> 10 wt.% mass loss in 56 days), high release of hydrocortisone (up to solubility limit) and biocompatibility ($> 80\%$ cell viability). The synthesized hydrogel coatings were also characterized with antimicrobial properties. However, before being used in clinical trials on humans, the developed materials must be first tested on animals to assess its impact on a living organisms.