



Slovak Society of Chemical Engineering  
Institute of Chemical and Environmental Engineering  
Slovak University of Technology in Bratislava

## PROCEEDINGS

51<sup>st</sup> International Conference of the Slovak Society of Chemical Engineering SSCHE 2025

Hotel DRUŽBA  
Jasná, Demänovská Dolina, Slovakia  
May 27 - 30, 2025

Editors: Assoc. Prof. Mário Mihaľ

ISBN: 978-80-8208-158-2, EAN: 9788082081582

Published by the Faculty of Chemical and Food Technology Slovak Technical University in Bratislava in Slovak Chemistry Library for the Institute of Chemical and Environmental Engineering; Radlinského 9, 812 37 Bratislava, 2025

Obalová, L., Leštinský, P., Maršolek, P., Vaštyl, J., Koumar, J., Korpas, J., Maxa, M.: Replacement of trichloroethylene in the extraction of crude caprolactam, Editors: Mihaľ, M., In *51st International Conference of the Slovak Society of Chemical Engineering SSCHE 2025*, Jasná, Demänovská Dolina, Slovakia, 2025.

## **Replacement of trichloroethylene in the extraction of crude caprolactam**

Lucie Obalová<sup>1</sup>, Pavel Leštinský<sup>1</sup>, Petr Maršolek<sup>1</sup>, Jana Vaštyl<sup>1</sup>, Jiří Koumar<sup>2</sup>, Jakub Korpas<sup>1</sup>,  
Milan Maxa<sup>2</sup>

<sup>1</sup>*Institute of Environmental Technology, CEET, VSB - Technical University of Ostrava, 17.  
listopadu 15/2172, 70800 Ostrava, Czech Republic*

<sup>2</sup>*TECHEM CZ Ltd., Bucharova 2657/12, 158 00 Praha 5, Czech Republic*

*e-mail: lucie.obalova@vsb.cz*

**Key words:** Caprolactam; Extraction; Mixed solvent; Trichloroethylene; Karr column

Caprolactam is the precursor to Nylon 6, a widely used synthetic polymer. Most of the world's caprolactam production involves its synthesis from cyclohexanone via the Beckmann rearrangement. The purity requirements for caprolactam are stringent, as even trace amounts of impurities can significantly affect the physical and mechanical properties of Nylon 6. Due to the presence of both polar and nonpolar impurities in crude caprolactam, purification traditionally includes forward extraction with a nonpolar solvent such as trichloroethylene, followed by back-extraction with water and multistage distillation.

This study focuses on the search for safer, non-carcinogenic alternatives to trichloroethylene in caprolactam extraction. Since a high distribution coefficient of caprolactam in the forward extraction process is undesirable for subsequent back-extraction with water, the alternative solvent should exhibit a distribution coefficient for caprolactam similar to that of trichloroethylene. Additionally, low mutual solubility with water, favorable physical properties, a low distribution coefficient for impurities, and acceptable cost are further requirements.

Suitable solvents were estimated using Hansen solubility parameters. Experimental liquid-liquid equilibrium data, along with key physical properties affecting mass transfer (density, viscosity, and interfacial tension), were determined for the design of Karr extraction columns with reciprocating plates, as used in caprolactam refining. The model was further validated through performance trials with an actual extraction unit employing trichloroethylene in caprolactam refining.

### **Acknowledgement**

This work was financially supported by the project "Continuous caprolactam refining" (No. TRIO FV40040.) Experimental results were accomplished by using Large Research Infrastructure ENREGAT supported by the Ministry of Education, Youth and Sports of the Czech Republic under project No. LM2018098.