



Slovak Society of Chemical Engineering
Institute of Chemical and Environmental Engineering
Slovak University of Technology in Bratislava

PROCEEDINGS

51st International Conference of the Slovak Society of Chemical Engineering SSCHE 2025

Hotel DRUŽBA
Jasná, Demänovská Dolina, Slovakia
May 27 - 30, 2025

Editors: Assoc. Prof. Mário Mihaľ

ISBN: 978-80-8208-158-2, EAN: 9788082081582

Published by the Faculty of Chemical and Food Technology Slovak Technical University in
Bratislava in Slovak Chemistry Library for the Institute of Chemical and Environmental
Engineering; Radlinského 9, 812 37 Bratislava, 2024

Tomasek, S., Egedy, A., Tóth, I., Lovas, L.: Modeling and Experimental study of LOHC systems based on toluene mixtures, Editors: Mihaľ, M., In *51st International Conference of the Slovak Society of Chemical Engineering SSCHE 2025*, Jasná, Demänovská Dolina, Slovakia, 2025.

Modeling and Experimental study of LOHC systems based on toluene mixtures

Szabina Tomasek^{1*}, Attila Egedy¹, István Tóth², László Lovas²

¹*Faculty of Engineering, Research Centre of Biochemical, Environmental and Chemical Engineering, University of Pannonia, Egyetem street 10, H-8200 Veszprém, Hungary*

²*Hungarian Gas Storage Ltd. Váci street 144-150, H-1138, Budapest, Hungary*

e-mail: tomasek.szabina@mk.uni-pannon.hu

Key words: Liquid Organic Hydrogen Carrier (LOHC), Hydrogenation, simulation study, parameter optimization

Hydrogen is one of the most promising energy carriers on the path toward a decarbonized future, due to its high energy density and clean combustion product. However, the efficient and safe storage of hydrogen remains a major technological challenge. Conventional storage methods are technologically complex, energy-intensive, and costly. A promising solution to overcome these disadvantages is the reversible binding of hydrogen to organic liquids, which enables chemically stable and safe storage (at atmospheric pressure and ambient temperature), while also allowing transportation via tankers, trucks, and pipelines.

In recent years, the applicability of various mono- and polycyclic aromatic compounds (e.g., toluene, n-ethylcarbazole, n-propylcarbazole, dibenzyl-toluene) and noble metal/oxide-supported and transition metal/oxide-supported catalysts has been investigated in LOHC systems. Among the carriers, toluene has been identified as the most suitable based on process parameters, and achievable conversions, while noble metal-based catalysts have proven to be the most favorable in terms of stability and selectivity.

The aim of the research work was to study and model the hydrogenation of toluene–methylcyclohexane mixtures, to analyze the effects of feedstock composition and process parameters, and to determine the optimal process conditions. A kinetic model was fitted to the experimental data, which served as the basis for constructing the reactor model for both hydrogenation and dehydrogenation. In both cases, the models showed a good fit to the experimental results.

This work has been implemented by the TKP2021-NKTA-21 project with the support provided by the Ministry of Culture and Innovation of Hungary from the National Research, Development and Innovation Fund, financed under the 2021 Thematic Excellence Programme funding scheme. the work was also supported by the Aquamarine Plus Project, Complex Implementation of an Energy Project Proposal – Hydrogen-Based Developments at Hungarian Gas Storage Ltd., VHFO/80/2023-EM_CONTRACT.