



Slovak Society of Chemical Engineering
Institute of Chemical and Environmental Engineering
Slovak University of Technology in Bratislava

PROCEEDINGS

51st International Conference of the Slovak Society of Chemical Engineering SSCHE 2025

Hotel DRUŽBA
Jasná, Demänovská Dolina, Slovakia
May 27 - 30, 2025

Editors: Assoc. Prof. Mário Mihaľ

ISBN: 978-80-8208-158-2, EAN: 9788082081582

Published by the Faculty of Chemical and Food Technology Slovak Technical University in Bratislava in Slovak Chemistry Library for the Institute of Chemical and Environmental Engineering; Radlinského 9, 812 37 Bratislava, 2025

Halabuk, L., Hribik, D., Markoš, J., Jelemenský, L.: Design of reactive spray absorption column for decarbonization of flue gas, Editors: Mihaľ, M., In *51st International Conference of the Slovak Society of Chemical Engineering SSCHE 2025*, Jasná, Demänovská Dolina, Slovakia, 2025.

Design of reactive spray absorption column for decarbonization of flue gas

Halabuk L., Hríbik D., Markoš J., Jelemenský L.

Department of Chemical and Biochemical Engineering, Faculty of Chemical and Food Technology, Slovak University of Technology in Bratislava, Radlinského 9, 812 37 Bratislava, Slovak republic

xhalabuk@stuba.sk

Key words: CO₂ absorption, spray tower, reactive absorption, droplet modelling, carbon dioxide capture

Absorption is a separation method in which one or more gaseous components are selectively transferred into a liquid phase through gas–liquid contact. Key performance factors include interfacial area, mass transfer coefficients in both phases, and the concentration or pressure gradient of the absorbed components. In practice, several types of absorption columns exist, with the most common being packed bed columns, bubble columns, and spray towers.

This project focuses on developing a mathematical model for a one-dimensional NaOH spray tower absorber. In this setup, NaOH–water solution droplets fall under gravity through an upward-flowing, CO₂-rich gas stream. Each droplet is modelled as a small reactor, with its size, temperature, and composition tracked as it absorbs CO₂, evaporates water, and reacts to form Na₂CO₃.

The core of the model consists of a system of ordinary differential equations (ODEs) that describe droplet motion, mass transfer of CO₂ and water, heat balance (including reaction and evaporation), and the chemical reaction between CO₂ and NaOH. The gas-phase composition is also updated along the tower height to reflect CO₂ depletion and water vapor enrichment. This problem is formulated as a boundary value problem (BVP), with conditions specified at both the top and bottom of the tower.

The model equations were solved numerically. By varying parameters such as tower height, initial droplet size and number, and NaOH concentration in the feed, the model predicts CO₂ removal efficiency and the extent of NaOH conversion to carbonate.

The author Lukáš Halabuk acknowledge the financial support from the Slovak Society of Chemical Engineering.